

DKS 380 Double Miter V-Notch Saw



Double Miter V-Notch Saw

- Contains horizontal and vertical clamps
- Two-hand start buttons to control the cutting cycle
- Electrical control box in the front
- Table and fence are nickel-plated to prevent profile marking
- Filter, regulator, lubricator air unit
- Contains separate clamping switch that engages the clamps
- Machine has two standard dust collection ports that are 100mm (4") diameter each
- Contains 1.5 kW / 2 HP motors
- Machine is 220 Volts / 3 HP, transformer required for other voltages / option 480 VAC
- Included sawblades are 380mm (15")
- Saw comes with simple infeed and outfeed supports
 1m (39.37") per side
- Machine contains full guarding on top around the pivoting heads and has guarding around the base to protect from cylinder movement
- Complete operator's manual with spare parts breakdown
- Complete electrical and pneumatic manual
- Includes machine tool kit





Technical Specifications DKS-380			
		IMPERIAL	METRIC
	Main Power Voltage	220 VAC	220 VAC
	Current	8 A	8 A
	Air Pressure	1.5ft³ @ 100 PSI	42.5L @ 7 bar
	Max. Profile Height	4.00"	101.60mm
	Max. Profile Width	3.75"	95.25 mm
	Machine Dimensions (LxW)	50" x 36"	1,270 x 914mm
	Machine Weight	734 lbs.	333 kg

Urban Machinery • 125 Werlich Drive • Cambridge, ON N1T 1N7
Tel.: (519) 624-080 • Fax: (519) 624-8588 • e-mail: sales@urban-machinery.com