

PRD 1, HTM 500

Test equipment



HTM 500



PRD 1

Our know-how is your advantage

PR 1 Corner tester with pressure gauge

- For control purposes in your production.
- To avoid injuries there are additional safety limit switches at the door, that switch off the machine immediately when the door is being opened.
- Jerk-free facturing of the corner to be tasted by a ram.
- The maximum force is recorded via the pressure gauge`s trailing pointer.




PRD 1 Corner tester with digital display

- The maximum force is shown on the digital display.
- Additionally, the values measured as a minimum and a maximum can be displayed and stored.
- Deletion of the individual measured values.
- Zero-point alignment.



Breaking strength...
thrust die with hydraulic cylinder






Carriage unit WG 1...
necessary for testing the
corner strength



HTM 500 Temperature measuring instrument

- For measuring the temperature et the heating element.
- From -20° to 300°C.
- Measurement accuracy +/- 2,5 K.
- With calbration and testing certificate.

 <p>PRD 1 = 65 kg WG = 14 kg</p>	 <p>PRD 1 = 230/400 L1-L2-L3-N-PE 0,2 kW</p>	 <p>PRD 1 / WG 1 LT = 800 / 565 mm B = 290 / 155 mm H = 870 / 85 mm</p>
---	---	--

Technical data apply to basic machine without options

Urban Machinery • 125 Werlich Drive • Cambridge, ON N1T 1N7
Tel.: (519) 624-0080 • Fax: (519) 624-8588 • e-mail: sales@urban-machinery.com

Visit us on the World Wide Web @ <http://www.u-r-b-a-n.com>